

HC Series



HC Series

The High Capacity (HC) series of refrigerators are designed for storing large quantities of a variety of materials at cryogenic temperatures. Temperatures generally range between -196°C (-320°F) at the liquid surface, and -190°C (-310°F) at the canister top.



HC Series

Models	HCL12	HC20	HC34	HC35	VHC35	
Static Holding Time days (1)	60	87	200	130	130	
Working Time days (2)	37	54	125	81	81	
Evaporation Rate (1) liters/days	0.20	0.23	0.17	0.27	0.27	
Liquid Nitrogen Capacity - liters	12	20	34	35	35	
Weight Empty	- lbs. - kg.	21.6 9.8	26.4 12.0	35.38 16.1	39 17.7	37.9 17.2
Weight Full (3)	- lbs. - kg.	43.0 19.5	62.0 28.2	95.9 43.6	101.3 46.0	100.2 45.5
Neck Diameter	- in. - mm.	3.6 91	3.6 91	3.6 91	4.7 119	4.7 119
Overall Height	- in. - mm.	19.0 482	24.25 615	26.31 668	26.8 681	26.8 681
Overall Diameter	- in. - mm.	15.6 396	15.6 396	18.8 478	18.8 478	18.8 478
Number of Canisters		6	6	6	10	6 (4)
Canister Dimensions	- in. - mm.	2.75x5 70x127	2.75x11 70x279	2.75x11 70x279	2.64x11 67x279	3.7x11 94x279
Number of 1.2 ml & 2.0 ml vials (5/cane)		NA	570	570	850	1050
Number of 1.2 ml & 2.0 ml vials (6/cane)		NA	684	684	1020	1260
Number of 1/2 cc straws - (10 per cane)		NA	1850	1850	2800	3000
Number of 1/2 cc straws - Bulk (1 level)		2940	NA	NA	NA	NA
Number of 1/2 cc straws - Bulk (2 levels)		NA	5880	5880	9800	9900
7th Canister		NA	NA	NA	NA	R036-9C27
Roller Base		R018-8C00	R018-8C00	R033-8C00	R033-8C00	R033-8C00
Cryo-Sentry Level Alarm		N/A	R034-8C15	R034-8C15	R037-8C15	R036-8C30

Features

- (1) Large storage capacity
- (2) New Rugged Construction – ribbed high strength aluminum body, magniformed necktube design, and more durable paint
- (3) Versatile storage system – convenient canister numbered index location ring and tapered internal spider
- (4) Superior vacuum performance with super insulation provides maximum holding times
- (5) Security – Optional low-level alarm is available with remote monitor and lockable lid
- (6) Mobility – Roller bases are available for all models



(1) Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.

(2) Work time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.

(3) Without canisters or racks.

(4) Optional 7th canister available to increase storage capacity by 23%.



Taylor-Wharton

A legacy of excellence. A vision of promise.

www.taylorwharton.com
salesandservice@taylorwharton.com

The Americas

Taylor-Wharton Cryogenics LLC

4075 Hamilton Boulevard
 Theodore, AL 36582
 Phone: +251-443-8680
 Phone: +800-898-2657

Australia

Taylor-Wharton Australia Pty. Ltd.

Unit 1/882 Leslie Drive
 Albury, NSW 2640
 Australia
 Phone: +61 (0)2 6040-2533

Europe

Taylor-Wharton Germany GmbH.

Postfach 1470
 D-25804 Husum
 Phone: +49 (0)4841-9850

Taylor-Wharton Slovakia s.r.o.

Vstupný areál U.S. Steel
 O44 54 Košice
 Slovakia
 Phone: +421 (0)55-727-7157

Asia

Taylor-Wharton (Beijing) Cryogenic Equipment Co. Ltd.

East End of Ping An Street
 Xianghe Economic Development Zone
 Xianghe City, Lang Fang Prefecture
 Hebei Province, PRC. 065402
 Phone: +86 (0)316-8219770

Taylor-Wharton Malaysia Sdn. Bhd.

Lot Nos. PT5073, 5076 & 5077
 Jalan Jangur 28/43
 Hicom Industrial Estate
 40400 Shah Alam
 Selangor Darul Ehsan
 Malaysia
 Phone: +60 (0)3-51913003

© 2012 Taylor-Wharton International. All rights reserved.