

LS Series



LS Series

The Taylor-Wharton Laboratory Systems (LS) are uniquely designed for large vial capacity in convenient box-type storage racks. They provide maximum holding times. This means lower per vial operating costs and fewer refills. The new LS6000 with the AutoTend Controller with temperature read out provides automatic filling and alarm features.



LS Series

Models	LS750	LS3000	LS4800	LS6000	LS6000AT	
Static Holding Time days (1)	130	106	153	194	194	
Working Time days (2)	80	66	96	120	120	
Evaporation Rate (1) liters/days	0.27	0.76	0.85	0.84	0.84	
Liquid Nitrogen Capacity - liters	35	81	130	165	165	
Weight Empty	- lbs. - kg.	39 17.7	70 31.8	90 40.9	121 55.0	121 55.0
Weight Full (3)	- lbs. - kg.	101.3 46.0	214.2 97.4	312.4 146.1	410.0 186.4	410.0 186.4
Neck Diameter	- in. - mm.	4.7 119	8.5 216	8.5 216	8.5 216	8.5 216
Overall Height	- in. - mm.	26.8 681	28.8 731	35.1 892	39.0 991	39.0 991
Overall Diameter	- in. - mm.	18.8 478	26.9 683	26.9 683	26.9 683	26.9 683
Number of Racks	6	6	6	6	6	
Number of Shelves/Rack	5	5	8	10	10	
2 ml vial capacity (4)	750	3000	4800	6000	6000	
Box Size - Shape Size in. Size mm. Vials per box (5)	Square 3.0 x 3.0 76x76 25	Square 5.0 x 5.0 127x127 100	Square 5.0 x 5.0 127x127 100	Square 5.0 x 5.0 127x127 100	Square 5.0 x 5.0 127x127 100	
Roller Base	R033-8C00	R05K-8C00	R05K-8C00	R05K-8C00	R05K-8C00	
Cryo-Sentry Level Alarm	R036-8C30	RS30-8C40	R05K-8C26	RS60-8C40	N/A	
Auto Tend Controller Kit	N/A	N/A	N/A	RS60-8C86	N/A	

Features

- (1) LS 6000 available with AutoTend Controller with temperature readout
- (2) LS 6000-AT, vapor phase, -190°C top of rack
- (3) New Rugged Construction – ribbed high strength aluminum body, magniformed necktube design, and more durable paint system
- (4) Convenient Storage Systems – rack index location ring and internal location spider, computer compatible box storage is ideal for simple inventory management
- (5) Superior vacuum performance with super insulation provides maximum holding times
- (6) Security – Accessory low-level alarm is available with remote monitor capability
- (7) Lockable lids
- (8) Mobility - Roller bases are available



(1) Evaporation rate and static holding time are nominal. Actual rate may be affected by the nature of the contents, atmospheric conditions, container history, and manufacturing tolerances.
 (2) Work time is an arbitrary, reference-only value to estimate container performance under the actual operating conditions.
 (3) Without canisters or racks.
 (4) 2.0 ml vial size: 12.5 mm O.D. internal thread
 (5) 81 cell boxes available



Taylor-Wharton

A legacy of excellence. A vision of promise.

www.taylorwharton.com
salesandservice@taylorwharton.com

The Americas

Taylor-Wharton Cryogenics LLC

4075 Hamilton Boulevard
 Theodore, AL 36582
 Phone: +251-443-8680
 Phone: +800-898-2657

Australia

Taylor-Wharton Australia Pty. Ltd.

Unit 1/882 Leslie Drive
 Albury, NSW 2640
 Australia
 Phone: +61 (0)2 6040-2533

Europe

Taylor-Wharton Germany GmbH.

Postfach 1470
 D-25804 Husum
 Phone: +49 (0)4841-9850

Taylor-Wharton Slovakia s.r.o.

Vstupný areál U.S. Steel
 O44 54 Košice
 Slovakia
 Phone: +421 (0)55-727-7157

Asia

Taylor-Wharton (Beijing) Cryogenic Equipment Co. Ltd.

East End of Ping An Street
 Xianghe Economic Development Zone
 Xianghe City, Lang Fang Prefecture
 Hebei Province, PRC. 065402
 Phone: +86 (0)316-8219770

Taylor-Wharton Malaysia Sdn. Bhd.

Lot Nos. PT5073, 5076 & 5077
 Jalan Jangur 28/43
 Hicom Industrial Estate
 40400 Shah Alam
 Selangor Darul Ehsan
 Malaysia
 Phone: +60 (0)3-51913003