

## Dual-Action Shaker KL 2 ↻ + ↔

The „2 in 1“ shaker

**Basic Equipment:** Basic device incl. rack system with 3 clamping strips h and rubber mat



Motion: can be switched from orbital to reciprocating  
Shaking platform: 300 x 300 mm  
Max. load: 2 kg  
Shaking speed: 30 - 420 rpm, steplessly adjustable  
Stroke: 8 mm  
Timer: 0 - 120 min / continuous

**KL 2**

**No. 6115 000**

### Accessories

Clamping strips for fastening other vessels see page 22

### Loading Capacity

Erlenmeyer flasks	250 ml	9 pieces
Separating funnels	250 ml	3 pieces

*Further loading possibilities see page 23*

### Technical Data

Electrical supply:	230 V or 115 V, 50 / 60 Hz please indicate in case of order
Enclosure protection:	IP 21
Heat emission:	approx. 7 - 10 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	355 x 455 x 195 mm
Weight:	13.5 kg

## Tilt Shaker WS 10 ↕

Slow, linear tilting motion

**Basic Equipment:** Basic device incl. basic tray and rubber mat



Motion: linear tilting motion  
Shaking platform: 340 x 340 mm  
Max. load: 10 kg  
Shaking speed: 1-23 rpm, steplessly adjustable  
Angle of tilt: 5° fixed  
Timer: 0 - 120 min / continuous

**WS 10**

**No. 6114 000**

### Rack Systems / Accessories

❶ Multi-storey rack system WS / TL	No. 0051 247
❷ Additional tray 340 x 340 mm	No. 0051 502
❸ Additional tray 340 x 500 mm	No. 0051 413

### Technical Data

Electrical supply:	230 V, 50 / 60 Hz 115 V version on request
Enclosure protection:	IP 21
Heat emission:	approx. 10 - 15 W
Ambient temperature:	5°C to 50°C
Relative humidity:	~ 85 %
Dimensions (w x d x h):	355 x 450 x 205 mm
Weight:	18.5 kg