

Compact Shaker KS 15 A control



Description

The programmable Orbital Shaker KS 15 A control with touch display for reproducible shaking tasks. The loading capacity is 15 kg on a shaking platform of 400 x 300 mm.

Basic Equipment

Basic device without rack system.

With touch display and programmable control.

Loading Capacity

Erlenmeyer flasks 100 ml	20 pieces
Erlenmeyer flasks 250 ml	12 pieces
Erlenmeyer flasks 500 ml	6 pieces

Erlenmeyer flasks 1000 ml 4 pieces
Separating funnels 250 ml 1 pieces

You will find further loading possibilities [here](#)

Options

[USB 2.0 interface](#)

[RS 232 interface](#)

[Control interface](#)

[Safety Package](#)

[Defined stop](#)

Details

Motion: orbital
Shaking platform: 400 x 300 mm
Max. load: 15 kg
Shaking speed: 30 - 420 rpm, in steps of 5
Stroke: 17 mm
Runtime: programmable / continuous
Order No.: 6170 000
Accessory: Aufsatz Combifix KS
Universaltablar KS
Inkubationshaube TH 15

Technical specifications

Electrical supply: 230 V or 115 V, 50 / 60 H please indicate in case of order
Enclosure protection: IP 21
Heat emission: approx. 7 W
Ambient temperature: 5°C to 50°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 510 x 490 x 150 mm
Weight: 19 kg